

PATENT APPLICATION SERIAL NO. _____

U.S. DEPARTMENT OF COMMERCE
PATENT AND TRADEMARK OFFICE
FEE RECORD SHEET

11/20/2001 GEBREGI 00000002 09988151
01 FC:101 740.00 OP
02 FC:103 666.00 OP

PTO-1556
(5/87)

11/19/01
111111 U.S. PTO
Please type a plus sign (+) inside this box →

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**UTILITY
PATENT APPLICATION
TRANSMITTAL**

(Only for new nonprovisional applications under 37 CFR 1.53(b))

Attorney Docket No. 016762.0217-US01

First Inventor Jamilly Pentz

Title DATA CARD

Express Mail Label No. _____

APPLICATION ELEMENTS

See MPEP chapter 600 concerning utility patent application contents.

1 Fee Transmittal Form (e.g., PTO/SB/17)
(Submit an original, and a duplicate for fee processing)

2. Applicant claims small entity status
See 37 CFR 1.27

3 Specification [Total Pages 24]
(preferred arrangement set forth below)
 - Descriptive title of the invention
 - Cross Reference to Related Applications
 - Statement Regarding Fed sponsored R & D
 - Reference to sequence listing, a table, or computer program listing appendix
 - Background of the Invention
 - Brief Summary of the Invention
 - Brief Description of the Drawings (if filed)
 - Detailed Description
 - Claim(s)
 - Abstract of the Disclosure

4 Drawing(s) (35 U.S.C. 113) [Total Sheets 11]

5 Oath or Declaration [Total Pages 3]
 a Newly executed (original or copy)
 b Copy from a prior application (37 CFR 1.63(d))
 (for continuation/divisional with Box 18 completed)
 i. DELETION OF INVENTOR(S)
 Signed statement attached deleting inventor(s) named in the prior application, see 37 CFR 1.63(d)(2) and 1.33(b)

6 Application Data Sheet See 37 CFR 1.76

ADDRESS TO:
Box Patent Application
Commissioner for Patents
Washington, DC 20231

7. CD-ROM or CD-R in duplicate, large table or Computer Program (Appendix)

8. Nucleotide and/or Amino Acid Sequence Submission (if applicable, all necessary)
 a Computer Readable Form (CRF)
 b. Specification Sequence Listing on:
 i. CD-ROM or CD-R (2 copies), or paper
 c. Statements verifying identity of above copies

ACCOMPANYING APPLICATIONS PARTS

9. Assignment Papers (cover sheet & document(s))

10. 37 CFR 3.73(b) Statement Power of Attorney
(when there is an assignee)

11. English Translation Document (if applicable)

12. Information Disclosure Statement (IDS)/PTO-1449 Copies of IDS Citations

13. Preliminary Amendment

14. Return Receipt Postcard (MPEP 503)
(Should be specifically itemized)

15. Certified Copy of Priority Document(s)
(if foreign priority is claimed)

16. Nonpublication Request under 35 U.S.C. 122 (b)(2)(B)(i)
Applicant must attach form PTO/SB/35 or its equivalent

17. Other

18. If a CONTINUING APPLICATION, check appropriate box, and supply the requisite information below and in a preliminary amendment, or in an Application Data Sheet under 37 CFR 1.76

Continuation Divisional Continuation-in-part (CIP) of prior application No. _____

Prior application information. Examiner _____ Group / Art Unit: _____

For CONTINUATION or DIVISIONAL APPS only. The entire disclosure of the prior application, from which an oath or declaration is supplied under Box 5b, is considered a part of the disclosure of the accompanying continuation or divisional application and is hereby incorporated by reference. The incorporation can only be relied upon when a portion has been inadvertently omitted from the submitted application parts.

19. CORRESPONDENCE ADDRESS

<input checked="" type="checkbox"/> Customer Number or Bar Code Label	26853	or <input type="checkbox"/> Correspondence address below	
Name	Covington & Burling Patent Docketing		
Address	1201 Pennsylvania Avenue, N.W.		
City	Washington	State D.C.	Zip Code 20004-2401
Country	USA	Telephone 202.662.6000	Fax 202.662.6291

Name (Print/Type)	Andrea G. Reister	Registration No. (Attorney/Agent)	36,253
Signature			Date November 19, 2001

11/19/01
JG978 U.S. PTO
09/98815111/19/01
111111 U.S. PTO

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

FEE TRANSMITTAL for FY 2002

Patent fees are subject to annual revision.

TOTAL AMOUNT OF PAYMENT (\$ 1,446.00)

Complete if Known

Application Number	Not Yet Assigned
Filing Date	Herewith
First Named Inventor	Jamily Pentz
Examiner Name	Not Yet Assigned
Group Art Unit	N/A
Attorney Docket No.	016762.0217-US01

METHOD OF PAYMENT

1. The Commissioner is hereby authorized to charge indicated fees and credit any overpayments to

Deposit Account Number 50-0740

Deposit Account Name

Charge Any Additional Fee Required Under 37 CFR 1.16 and 1.17 Applicant claims small entity status See 37 CFR 1.27

2. Payment Enclosed

Check Credit Card Money Order Other

FEE CALCULATION (continued)

3. ADDITIONAL FEES

Large Entity	Small Entity	Fee Description	Fee Paid
Fee Code	Fee (\$)	Fee Code	Fee (\$)
105	130	205	65
127	50	227	25
139	130	139	130
147	2,520	147	2,520
112	920*	112	920*
113	1,840*	113	1,840*
115	110	215	55
116	400	216	200
117	920	217	460
118	1,440	218	720
128	1,960	228	980
119	320	219	160
120	320	220	160
121	280	221	140
138	1,510	138	1,510
140	110	240	55
141	1,280	241	640
142	1,280	242	640
143	460	243	230
144	620	244	310
122	130	122	130
123	50	123	50
126	180	126	180
581	40	581	40
146	740	246	370
149	740	249	370
179	740	279	370
169	900	169	900
Other fee (specify)			
*Reduced by Basic Filing Fee Paid		SUBTOTAL (3) (\$ 40.00)	

SUBTOTAL (1) (\$ 740.00)


2. EXTRA CLAIM FEES		Extra Claims	Fee from below	Fee Paid
Total Claims	57	-20** =	37 X 18.00	= 666.00
Independent Claims	3	-3** =	0 X 0.00	= 0.00
Multiple Dependent				

Large Entity		Small Entity		Fee Description
Fee Code	Fee (\$)	Fee Code	Fee (\$)	
103	18	203	9	Claims in excess of 20
102	84	202	42	Independent claims in excess of 3
104	280	204	140	Multiple dependent claim, if not paid
109	84	209	42	** Reissue independent claims over original patent
110	18	210	9	** Reissue claims in excess of 20 and over original patent
SUBTOTAL (2) (\$ 666.00)				

** or number previously paid, if greater. For Reissues, see above

SUBMITTED BY

Complete (if applicable)

Name (print/type)	Andrea G. Reister	Registration No (Attorney/Agent)	36,253	Telephone	(202) 662-6000
Signature				Date	November 19, 2001

11/19/01
J1133 U.S. PTO

Docket No.: 016762.0217-US01
(PATENT)

Jc978 U.S. PTO
09/988151
11/19/01

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of: Jamily Pentz, et al.

Application No.: Not Yet Assigned

Group Art Unit: N/A

Filed: Herewith

Examiner: Not Yet Assigned

For: DATA CARD

TRANSMITTAL LETTER

Commissioner for Patents
Washington, DC 20231

Dear Sir:

Enclosed are the following items for filing in connection with the above-referenced
Patent Application:


1. Utility Patent Application Transmittal (1 page) (PTO/SB/05);
2. Fee Transmittal for FY 2002 (1 page) (PTO/SB/17);
3. Utility Patent Application comprising 17 pages of specification; 6 pages of claims (claims 1-57); a one-page abstract; and 11 pages of drawings (Figs. 1a, 1b, 2a, 2b, 3a, 3b, 4a-4d, 5a, 5b, 6a, 6b, 7a-7c, 8a, 8b, 9a-9c, 10-12, 13a, 13b);
4. Declaration for Utility or Design Patent Application (3 pages) (PTO/SB/01 and PTO/SB/02A);
5. Application Data Sheet (3 pages);
6. Recordation Form Cover Sheet (1 page) (PTO-1595);
7. Assignment by Inventors (8 pages);
8. Statement Under 37 C.F.R. 3.73(b) (1 page with copy of assignment attached);

9. Power of Attorney from Assignee (2 pages);
10. Check No. 287653 in the amount of \$1446 to cover \$740 basic filing fee; \$666 excess claim fee; and \$40 assignment recordation fee;
11. Two return receipt postcards.

The Commissioner is hereby authorized to charge any deficiency in the fees filed, asserted to be filed or which should have been filed herewith (or with any paper hereafter filed in this application by this firm) to our Deposit Account No. 50-0740, under Order No. 016762.0217-US01. A duplicate copy of this paper is enclosed.

Dated: November 19, 2001

Respectfully submitted,

By 
Andrea G. Reister

Registration No.: 36,253
COVINGTON & BURLING
1201 Pennsylvania Avenue, N.W.
Washington, DC 20004-2401
(202) 662-6000
Attorneys for Applicant

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
APPLICATION FOR U.S. LETTERS PATENT

Title:

DATA CARD

Inventors:

Jamily Pentz; Emmet Burns; Richard J. Collins; R. B. Montgomery; and A. A. Kendle

Andrea G. Reister
COVINGTON & BURLING
1201 Pennsylvania Avenue, N.W.
Washington, DC 20004-2401
(202) 662-6000

TITLE OF INVENTION

[0001] DATA CARD

CROSS-REFERENCE TO RELATED APPLICATIONS

[0002] This application claims priority under 35 U.S.C. § 119(e) to U.S. Provisional Application No. 60/263,756, filed January 25, 2001 and claims priority under 35 U.S.C. § 120 to U.S. Patent Application No. 09/611,320, filed July 6, 2000, and to Design Application Nos. 29/141,685, 29/141,652, 29/141,645, 29/141,642, 29/141,688, 29/141,704, 29/141,703, 29/141,691, 29/141,702, 29/141,692, 29/141,701, 29/141,700, 29/141,693, 29/141,699, filed May 11, 2001 and 29/142,203, filed May 22, 2001, the entirety of each of the foregoing applications being incorporated herein by reference.

STATEMENT REGARDING FEDERALLY SPONSORED

RESEARCH OR DEVELOPMENT

[0003] Not Applicable

REFERENCE TO A MICROFICHE APPENDIX

[0004] Not Applicable

BACKGROUND OF THE INVENTION

[0005] Field of the Invention. This invention relates generally to data cards, such as credit cards, that contain a magnetic stripe or other means of storing information. More particularly, this invention relates to such cards that are small in size.

[0006] Related Art. Cards of various kinds have become ubiquitous in modern society. People often carry a number of cards in their wallet or carrying case, including credit cards, ATM or bank cards, debit cards, "smart cards," insurance cards, a driver's license, identification cards, telephone calling cards, transit cards, library cards, and card-entry hotel keys. An increasing number of consumer transactions require use of these cards, for example, as the form of payment, or as identification necessary for another form of payment or admission.

Quick and accurate access to certain individual cards is useful and desirable for both the consumer and the vendor of goods or services.

[0007] Typically, consumers store credit cards and other types of cards in a wallet or carrying case. These wallets and carrying cases are frequently equipped with sleeves or slots for holding one or more cards in an arrangement selected by the user. Because of the proliferation of the types and numbers of cards carried by consumers, cards are often held very tightly within these sleeves or slots, making retrieval of a particular card difficult. Difficulty in removing a single selected card increases the time necessary for the transaction, causes stored cards to be frequently reshuffled and potentially disorganized, and increases the likelihood that cards will be dropped or lost.

[0008] While the number of cards typically carried by consumers is increasing, most consumers use certain types of cards much more frequently than others. For example, some consumers may use a credit card for nearly every sales transaction, but only rarely, if ever, use calling cards, library cards, or insurance cards. Because a subset of the total number of cards carried by consumers must be accessed repeatedly, it is particularly desirable to improve the accessibility of these types of cards.

[0009] One way to improve accessibility of frequently used cards is by allowing them to be stored in a separate location from the traditional wallet or carrying case. Such cards could be stored on key-chains, lanyards, hooks, or other similar devices that are easily retrieved from a bag or pocket. Thus, when a consumer needs to use the card during a transaction, the card may be quickly retrieved and given to the merchant. This provides an added level of convenience to the consumer by making the payment process quicker and simpler. Additionally, the merchant is able to move customers through the line more quickly, improving customer satisfaction. An additional benefit of storing frequently used cards on a key-chain or like device is that the possibility that the card will be lost is decreased. This is because a single card is much more easily misplaced than a card attached to a key-chain.

[0010] Conventionally sized cards, however, are too large and cumbersome to be conveniently stored on a key-chain or like device. The individual items on a key chain must be small and compact so that the key-chain can accommodate numerous items. Further, key-chains

and the like are often placed in the pockets of clothing, which may be small. Finally, larger items, such as conventional credit cards, could be bent or otherwise damaged when stored on a device such as a key-chain. Thus, for a card to be effectively carried on a key-chain, its size must be significantly reduced.

[0011] The degree to which conventional cards may be reduced in size, however, is limited by the requirements of standard magnetic stripe card readers, such as point-of-sale ("POS") terminals through which the user "swipes" the card to make a purchase or payment. In order to ensure interoperability between the magnetic stripe readers and cards bearing magnetic stripes, the parameters defining the magnetic stripe are governed by the International Organization for Standardization (ISO) and the International Electrotechnical Commission (IEC). ISO/IEC 7811 provides standards for the physical characteristics of the magnetic stripe including the location of the stripe on the card, the surface profile of the stripe, and the height of the stripe above the card surface. It would be advantageous for a reduced-size card to comply with ISO/IEC 7811, or otherwise be compatible with existing card readers and POS terminals.

[0012] Proper functioning of the magnetic stripe is very important. On conventional cards, such as credit cards, magnetic stripes contain encoded information that electronic readers can read to perform a function or confirm identification. For example, on credit and debit cards, the magnetic stripe is usually encoded with specific account information such as the credit card number, cardholder's name, the card expiration date, and a personal identification code. If the electronic device for reading the encoded information cannot properly read the magnetic stripe, the vendor must enter the information manually, using a keypad, telephone, or other similar device. Manually entering the encoded information adds both indirect and direct costs to the vendor. For example, the additional time necessary to enter the information manually may increase needs for register operators and decrease the vendor's ability to attend to other customer matters. In addition, vendors are frequently charged increased transaction fees by the card issuer for a manually entered transaction.

[0013] Thus, a need exists for providing cards, such as credit cards, that are reduced in size from currently used cards, and yet still are operable with currently used readers. Such a card would greatly enhance the efficiency of frequent transactions, including sales transactions, by allowing regularly used cards to be readily and easily retrieved. Further,

because such a card could be readily stored on a key-chain or like device, the probability that the card would be lost or misplaced is reduced. Finally, because such a card would be compatible with currently used readers, no redesign of existing card reader technology would be required.

BRIEF SUMMARY OF THE INVENTION

[0014] In one aspect, the present invention provides a data card that is reduced in size from conventional credit-card-sized cards, and contains an information storage medium, such as a magnetic stripe or a computer chip, that can be read by existing card reader technology.

[0015] In another aspect, a reduced-size data card is provided with a magnetic stripe, which is located near an edge of the card, on which data is encoded. Such a magnetic stripe is reduced in size from the magnetic stripes found on conventionally sized cards, and contains data encoded at a higher bit density than on conventionally sized cards. The magnetic stripe is compatible with existing card reader technology.

[0016] In yet another aspect, a reduced-size data card is provided with a hole to allow key-chain storage, and the core may be composed, at least in part, of polyester. Additionally, the surface of a data card of the present invention may also be provided with raised dimples or craters to enhance gripability of the card. Further, information may be printed on the surface of the card, in order to reduce or eliminate the need to emboss the card with raised lettering or embossing.

[0017] In still another aspect, a reduced-size data card of the present invention may have an angled edge.

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] FIG. 1A is an illustration of the front view of a conventional credit card.

[0019] FIG. 1B is an illustration of the back view of a conventional credit card.

[0020] FIG. 2A is an illustration of the front view of one preferred embodiment of the reduced-size data card of the present invention.

[0021] FIG. 2B is an illustration of the back view of the embodiment shown in FIG. 2A.

[0022] FIG. 3A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

[0023] FIG. 3B is an illustration of the back view of the embodiment shown in FIG. 3A.

[0024] FIG. 4A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

[0025] FIG. 4B is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

[0026] FIG. 4C is an illustration of the back view of the embodiment shown in FIG. 4A.

[0027] FIG. 4D is an illustration of an alternate back view of the embodiment shown in FIG. 4A.

[0028] FIG. 5A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

[0029] FIG. 5B is an illustration of the back view of the embodiment shown in FIG. 5A.

[0030] FIG. 6A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

[0031] FIG. 6B is an illustration of the back view of the embodiment shown in FIG. 6A.

[0032] FIG. 7A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention

[0033] FIG. 7B is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention

[0034] FIG. 7C is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention

[0035] FIG. 8A is a partial sectional view of another preferred embodiment of the reduced-size data card of the present invention taken through the tread where the tread includes raised dimples.

[0036] FIG. 8B is a partial sectional view of another preferred embodiment of the reduced-size data card of the present invention taken through the tread where the tread includes craters.

[0037] FIG. 9A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

[0038] FIG. 9B is an illustration of the back view of the embodiment shown in FIG. 9A.

[0039] FIG. 9C is an illustration of a side view of the embodiment shown in FIG. 9A.

[0040] FIG. 10 is an illustration of the ISO/IEC 7811 standards for location and width of magnetic stripe data tracks 1 and 2.

[0041] FIG. 11 is an illustration of the ISO/IEC 7811 standards for location and width of magnetic stripe data track 3.

[0042] FIG. 12 is an illustration of the ISO/IEC 7811 standards for magnetic stripe location and size.

[0043] FIG. 13A is an illustration of the front view of another preferred embodiment of the reduced-size data card of the present invention.

[0044] FIG. 13B is an illustration of the back view of the embodiment shown in FIG. 13A.

DETAILED DESCRIPTION OF THE INVENTION

[0045] Reference will now be made to the present preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings.

[0046] FIGs. 1A-B illustrate one embodiment of a conventional credit card. FIG. 1A shows the front side of a conventional standard size credit card 10, which is typically embossed using raised lettering with a credit card number 11, an expiration date 12, and the name of the card-holder 13. Such a card also usually contains the name of the issuing bank 14, and the credit card company, such as American Express®, MasterCard®, or VISA®, 15. It may also contain other information, such as sponsor logos and/or a “platinum” or similar indication. Additionally, the credit card may contain an identification photograph of the card-holder for security purposes. The back side of conventional card 10, shown in FIG. 1B, typically contains a box 16 that can be signed by the card holder, which is used for verification purposes when a purchase is made. Additionally, the back side of card 10 contains a magnetic stripe 17, which runs parallel to the card’s largest dimension. Magnetic stripe 17 stores information, such as credit card number, that can be read by conventional point of sale (“POS”) terminals. A standard credit card is approximately 3 3/8 in. long by 2 1/4 in. high, for an aspect ratio (length/height) of approximately 1.5, and has a thickness of approximately 0.75 mm.

[0047] The card of the present invention includes an information storage medium. By “information storage medium,” is meant a medium that is added to the card that stores information in a magnetic, electronic, or electro-magnetic manner. This term does not include printed information either affixed to or printed directly on the card. Exemplary information storage media suitable for use with the present invention include, but are not limited to, magnetic stripes and computer chips.

[0048] FIGs. 2A-B depict a preferred embodiment of the present invention, including a generally rectangular card 20, a magnetic stripe 21, and a hole 22. The dimensions of card 20 are approximately 2 1/8 in. long by 1 1/4 in. high, for an aspect ratio (length/height) of approximately 1.7, and a thickness of approximately 0.75 mm. This is a significant reduction

from the dimensions of a standard credit card. As would be appreciated by one skilled in the art, the foregoing specific dimensions are representative only, and the present invention is not limited to any particular dimensions. Preferably, the present invention is carried out using cards with dimensions ranging in length from approximately 1 in. to 3 in., and ranging in height from approximately 1 in. to 1 7/8 in. Thus, the aspect ratio (length/height) could range from approximately 0.53 (1 / 1.875) to 3 (3 / 1).

[0049] Magnetic stripe 21 is located on the back side of card 20, as shown in FIG. 2B, and is oriented perpendicularly to the card's largest dimension. Alternatively, the magnetic stripe could be located on the front side of card 20. In one embodiment of the present invention, magnetic stripe 21 is approximately 0.41 in. in width. In another embodiment, shown for example in FIGs. 3A-B, magnetic stripe 31 is approximately 0.25 in. in width.

[0050] ISO/IEC 7811 provides standards for the location of the stripe on the card, the surface profile of the stripe, and the height of the stripe above the card surface. Generally, designers of cards attempt to comply with these standards to ensure compatibility with existing POS terminals. Unexpectedly, the card of the present invention is compatible with existing point of sale terminals without complying with several aspects of the ISO/IEC standards, as explained in more detail below.

[0051] Finally, hole 22 is shown as located in a corner of card 20, and allows the card to be readily carried on a key-chain or like device. It should be apparent to one skilled in the art that hole 20 can be located anywhere on the card that allows the card to be carried by a key-chain or similar device and does not interfere with the magnetic stripe.

[0052] FIGs. 3A-B show an alternate preferred embodiment. Like the previous embodiment, this embodiment includes a generally rectangular card 30, a magnetic stripe 31, that is oriented perpendicularly to the card's largest dimension, and a hole 32. Here, however, magnetic stripe 31 is narrower in width than magnetic stripe 21 of FIG. 2B. A narrower magnetic stripe may be utilized when less information is needed to be stored by the magnetic stripe or when encoding techniques allow more information to be stored in a reduced space.

[0053] FIGs. 4A-D show alternate preferred embodiments. FIG. 4A shows a generally rectangular shaped card 40 with a hole 42. Card dimensions (2 1/8 in. by 1 1/4 in.) are

shown on FIG. 4A and are significantly reduced from the standard size credit card. Additionally, card 40 contains an identification photograph 43, various logos 44 and 45, and additional information 46. Further, embossed information, such as credit card number or expiration date (not shown) could be included. Other arrangements of logos, and information should be apparent to one of ordinary skill in the art from this description or from practice. For example, FIG. 4B shows card 40', which is similar to card 40 (FIG. 4A) but without the identification photograph, and with a different arrangement of logos and other information.

[0054] FIG. 4C shows the back side of card 40, depicted in FIG. 4A, which includes magnetic stripe 41 oriented perpendicularly to the card's largest dimension. Additionally, FIG. 4C includes signature block 47. Signature block 47 is to be signed by the card holder, and is used for signature verification when a purchase is made. Finally, the back side of card 40 may contain logos 48 and other information, as would be apparent to one of ordinary skill in the art.

[0055] FIG. 4D shows an alternate arrangement of the back side of card 40. It shows magnetic stripe 41' which is narrower than magnetic stripe 41 of FIG. 4C. Narrower magnetic stripes may be utilized when less information is required to be stored by the magnetic stripe, or when encoding techniques allow more information to be stored in less space.

[0056] FIGs. 5A-B show an alternate preferred embodiment, including a generally rectangular shaped card 50 and a magnetic stripe 51, oriented perpendicularly to the card's largest dimension. Unlike previous embodiments, the present embodiment does not contain a hole. While a hole is a helpful way to attach a card of the present invention to a key-chain or like device, such a hole is not required. Thus, the card can be attached to the key-chain by a clip or similar device. Additionally, the card of the present invention is not required to be stored on a key-chain or like device and could be stored in any fashion chosen by the consumer, such as directly in the consumer's pocket or bag. It should be readily apparent to one skilled in the art that any of the embodiments described herein could be modified such that the hole is removed.

[0057] FIGs. 6A-B show still another alternate preferred embodiment, including a generally rectangular shaped card 60, a magnetic stripe 61, and a hole 62. Magnetic stripe 61 is oriented parallel to the card's largest dimension. As described above, magnetic stripe 61 is

preferably compatible with existing magnetic stripe readers. Magnetic stripe 61 may be either narrow or wide, depending on the amount of data required to be stored and the degree of data compression. Because magnetic stripe 61 is oriented parallel to the card's longest dimension, it may be capable of storing a greater amount of information at a given width than magnetic stripe 21 of FIG. 2B which is oriented perpendicularly to the card's largest dimension. Thus, the present embodiment may be more easily implemented when greater amounts of information storage is required. It should be readily apparent to one of ordinary skill in the art that any of the embodiments described herein could be modified such that the magnetic stripe is oriented parallel to the card's largest dimension.

[0058] Conventional credit cards and the like have been generally rectangular in shape. However, the card of the present invention may take on other shapes. For example, the card could be any number of geometric shapes such as triangular or trapezoidal. Additionally, the card could take on the shape of naturally occurring or human-made objects, such as pine trees or airplanes. Such shapes could be related to the card issuer or sponsor. Thus, a credit card that a consumer can use to accrue frequent flier miles could be in the shape of an airplane. The dimensions of such cards generally comport with the size guidelines suggested herein. Because such cards are not rectangular, the magnetic stripe would not necessarily be oriented as described above (either parallel to or perpendicular to the card's largest dimension). Thus, the magnetic stripe could be oriented in any number of ways, depending on the shape of the card.

[0059] Additionally, any of the embodiments described herein could be provided with a tread to increase the gripability of the card. Such treads are described in detail in U.S. Patent Application No. 09/611,320 filed on July 6, 2000, the entirety of which is hereby incorporated by reference.

[0060] These treads could take the form of a plurality raised dimples disposed on a surface of the card. The treads are preferably disposed on the surface or face of the card that comes into contact with the user to increase gripability. FIGs. 7A-C show three alternate preferred embodiments of the present invention in which the surface of the card is provided with treads. In each a number of dimples 77 is arranged to form a plurality of treads 76 on the front face 71 of card 70. In FIG. 7A, the dimples 77 are arranged to form treads 76 in either a triangular pattern or a line. The dimples 77, however, can also be arranged in any number of

patterns. As depicted in FIGs. 7A-7C, the treads 76 are located near an edge 73 of card 70, and in each preferred embodiment depicted in FIGs. 7A-7C, a tread 76 is located near the top edge 72 of the card 70. Other arrangements of dimples 77 forming treads 76 should be apparent to one of skill in the art from this description of from practice of the invention depending on the intended or experienced use of the card.

[0061] FIG. 8A shows a sectional view of a preferred embodiment of card 70 of the present invention taken along the line X-X of FIG. 7A, in which the dimples 77 are raised from the front face 71 of the card 70. In such an embodiment, the height of each dimple should be selected so as not to interfere with the proper operation of POS terminals or other devices that require the card to be swiped by or through the device.

[0062] FIG. 8B shows a sectional view of an alternate preferred embodiment of card 70 of the present invention. In this embodiment, the dimples are created in such a manner as to create individual craters 77 in which the lip of the crater is raised slightly above the front surface 71 of the card 70, while the center of the crater is slightly below the surface of the card.

[0063] While the specific embodiments described herein are cards having magnetic stripes such as credit cards, debit cards, and bank cards, this is by way of example, and the invention is not limited to these types of cards. Thus, the present invention can be implemented for many different types of data cards including Smart Cards (i.e. cards containing computer chips that store information), stored value cards, proximity chip cards, and other cards that are capable of storing information. A detailed discussion of data cards containing embedded computer chips may be found in U.S. Patent No. 4,443,027 to McNeely et al., the entirety of which is hereby incorporated by reference.

[0064] Another preferred embodiment of the present invention will now be described in greater detail. This preferred embodiment, shown in FIGs. 9A-C, includes a generally rectangular card 90, a magnetic stripe 91, and a hole 92. The front face 93 of card 90 is shown in FIG. 9A; the rear face 94 of card 90 is shown in FIG. 9B. Approximate dimensions of card 90, as indicated on FIG. 9B, are 1 9/16 inches (height) by 2 9/16 inches (length). The width of the card, shown in FIG. 9C (not to scale), is approximately 0.75 mm. These height and

length dimensions are reduced from conventionally-sized credit card dimensions, which are approximately 2 1/4 inches (height) by 3 3/8 inches (length).

[0065] Once again, the specific dimensions of card 90 are representative only, and the present invention is not limited to any particular dimensions. Nevertheless, the present invention is preferably carried out using cards with dimensions ranging from approximately 1 inch by 1 inch to approximately 1 7/8 inches to 3 inches.

[0066] The front face 93 of card 90 contains various information such as card number 95, expiration date 96, and card-holder name 97. This information may be embossed on the card. In a preferred embodiment, the card is free from or devoid of embossing or other raised lettering. In such an embodiment, the information may be printed on the card using laser printing techniques, as are known in the art.

[0067] Between front and rear faces 93 and 94 of card 90 is a core 99, as shown in FIG. 9C. This core may be composed of, at least in part, polyester. In one embodiment, the core is composed of 80% polyester and 20% polyvinyl chloride (PVC). The use of polyester in the core is advantageous because it increases the durability of the card. As would be apparent to one skilled in the art, various percentages of polyester and other materials may be used for the card core.

[0068] In the embodiment shown in FIGS. 9A-C, magnetic stripe 91 is positioned parallel to the bottom edge 98 of card 90. The bottom edge, of course, is defined with respect to the particular card orientation shown in FIG. 9B. As would be readily apparent to one skilled in the art, rotation of card 90 could cause "bottom" edge 98 to appear as if it is a right, left, or top edge. Magnetic stripe 91 is used to store encoded data such as the name of the card-holder, a credit card or other account number, card expiration date, and a personal identification code or other security information. The lengthwise dimension of magnetic stripe 91 is approximately 2 9/16 inches. As defined herein, the lengthwise dimension of a magnetic stripe is the largest dimension of the magnetic stripe. However, as described above, the present invention is not limited to any particular dimensions. Preferably, the lengthwise dimension of the magnetic stripe ranges from approximately 1 inch to approximately 3 inches.

[0069] The requirements of ISO/IEC 7811, which specifies the international standards for magnetic stripes will now be discussed, and then compared to the characteristics of magnetic stripe 91 of the present invention. Designers of cards bearing magnetic stripes attempt to comply with the standards set forth in ISO/IEC 7811 in order to ensure compatibility and interoperability with current magnetic stripe readers and POS terminals.

[0070] ISO/IEC 7811 specifies that a magnetic stripe may contain up to three tracks of encoded information. As will be appreciated by one skilled in the art, each track is essentially a strip of specified width and location running the length of the magnetic stripe, on which data is encoded. According to ISO/IEC 7811, track 1 is located closest to the edge of the card and contains data encoded at 210 bits per inch (bpi). Track 2 is adjacent to track 1 and contains data encoded at 75 bpi. FIG. 10 shows the width and location of tracks 1 and 2 as specified by ISO/IEC 7811-4, the entirety of which is hereby incorporated by reference. Track 3 is the furthest from the edge of the card and contains data encoded at 210 bpi. FIG. 11 shows the width and location of track 3 as specified by ISO/IEC 7811-5, the entirety of which is hereby incorporated by reference.

[0071] In all cases, data is encoded on the tracks using two-frequency encoding, as specified in ISO/IEC 7811. As will be understood by one skilled in the art, two-frequency encoding involves the use of flux transitions to encode data. The encoding comprises data and clocking transitions together. The presence of a flux transition between clocking transitions signifies that the bit is a "one;" the absence of a flux transition signifies a "zero." Additional detailed discussion of two-frequency encoding may be found in ISO/IEC 7811-2 and 7811-6, the entirety of which is incorporated herein by reference.

[0072] Each track of data contains a "start sentinel." The start sentinel is the first data bit, and indicates the beginning of the encoded data on each track. As shown in FIG. 12, ISO/IEC 7811 specifies that the location of the start sentinel is approximately 0.293 inches from the right side of the card for all tracks.

[0073] FIG. 12 shows additional physical characteristics for magnetic stripes, as specified by ISO/IEC 7811. The minimum length of the magnetic stripe is specified as 3.135 inches (3.250 inches minimum from the right edge of the card to the left edge of the stripe minus

the 0.115 inches maximum from the right edge of the card to the right edge of the stripe). The minimum width of the magnetic stripe is 0.25 inches for cards using tracks 1 and 2, and 0.41 inches for cards using all three tracks.

[0074] Magnetic stripe 91 (FIG. 9B) is different in several respects from the magnetic stripes specified by ISO/IEC 7811. First, the length of magnetic stripe 91 is approximately 2 9/16 inches, significantly shorter than the 3.135 inch minimum length specified by ISO/IEC 7811.

[0075] Second, the data on magnetic stripe 91 is encoded at bit densities higher than those prescribed in ISO/IEC 7811. Magnetic stripe 91 contains data encoded on tracks 1 and 2. In order to ensure that sufficient data is encoded in the smaller magnetic stripe area, data is encoded on track 1 at 260 bpi and on track 2 at 100 bpi. Both of these bit densities are significantly higher than those specified in ISO/IEC 7811 for tracks 1 and 2 (210 bpi and 75 bpi, respectively). As should be appreciated by one skilled in the art, data could also be encoded on track 3 if necessary or desirable in a particular circumstance. It should also be noted that the present invention is not limited by these specific bit densities, and other bit densities could be selected that ensure the storage of the appropriate amount of information in the available space.

[0076] Also, as shown in FIG. 9B, the start sentinel of magnetic stripe 91 is located 0.200 inches from the right edge of card 90. This start sentinel location is significantly different from that specified in ISO/IEC 7811, which specifies that the start sentinel must be located 0.293 inches from the right edge of the card.

[0077] Preferably, the data on tracks 1 and 2 of magnetic stripe 91 is encoded using standard two-frequency encoding. However, it should be understood by one skilled in the art that the present invention is not limited to a particular encoding technique. Preferably, the width of each track and the distance of each track from the bottom edge 98 of card 90 complies with the requirements of ISO/IEC 7811, as described above and shown in FIG. 10.

[0078] The dimensions of card 90 itself are different from the dimensions specified in ISO/IEC 7810, the entirety of which is hereby incorporated by reference, which generally specifies physical parameters of identification cards. Notably, ISO/IEC 7810 establishes

minimum dimensions for identification cards at 2.125 inches by 3.370 inches. The dimensions of card 90 are approximately 1 9/16 inches by 2 9/16 inches.

[0079] Given that card 90 of the present invention does not comply with numerous standards and specifications set forth in ISO/IEC 7810 and 7811, it would be expected by those skilled in the art that the card would not be operable with standard magnetic stripe readers and POS terminals. However, tests performed on prototype cards indicate that the data cards of the present invention are compatible with standard equipment.

[0080] In order to test the prototype cards, twenty-five cards, substantially similar to that shown in FIGs. 9A and 9B and described above, were assembled and encoded with twenty-five different accounts. These twenty-five cards were then tested using five different POS terminals. The five POS terminals were standard merchant POS terminals manufactured by VeriFone Inc. A number of the twenty-five cards were tested on each of the five POS terminals. In order to ensure proper reading of the card, two tests were performed. First, after swiping each test card through the terminal, the terminal attempted to print a receipt showing, among other things, the name associated with the account encoded on each card. Second, the terminal used the data obtained from the card, and attempted to access the interchange system and obtain authorization for a transaction. All tested cards passed both tests. This testing indicates that the data card of the present invention is unexpectedly compatible with POS terminals, despite the non-compliance with numerous aspects of ISO/IEC 7810 and 7811.

[0081] Additional testing was carried out using cards similar to card 130, shown in FIGs. 13A and 13B. Card 130 differs from card 90 only in that edge 139 of card 130 is angled. The same testing protocol described above was performed on twenty-five cards substantially similar to card 130 as shown in FIGs. 13A and B. The magnetic stripe 131 on card 130 is substantially the same as magnetic stripe 91 of card 90 (FIG. 9B). All cards tested passed both the receipt and authorization tests.

[0082] Thus, testing the prototype cards of various embodiments reveals that cards of the present invention are interoperable with magnetic card reader technology and POS terminals despite non-compliance with several of the relevant ISO/IEC standards.

[0083] Now will be described a method of use for a reduced-size data card of the present invention. As described above, such a card may be stored on a key-chain, lanyard, hook or similar device. Alternatively, the card may simply be placed in the pocket or bag of a consumer. When a consumer carrying a card of the present invention approaches a POS terminal or other card reader, such as when making sales transaction, the consumer may be required to produce the card to complete the transaction. Because of the convenience of storage, the consumer quickly and easily retrieves the card, and either gives the card to the merchant to "swipe" through the reader, or the consumer may be permitted to "swipe" the card him/herself. The POS terminal or other card reader then "reads" the encoded information on the card, such as card number, credit limit or the like, and the transaction is completed. The card may then be restored by the consumer until the next usage.

[0084] Although particular embodiments of the invention have been described and illustrated herein, it is recognized that modifications and variations may readily occur to those skilled in the art, and consequently it is intended that the claims be interpreted to cover such modifications and equivalents.

CLAIMS

What is claimed as new and desired to be protected by Letters Patent of the United States is:

1. A data card comprising a first face, a second face, and an information storage medium, wherein said card has dimensions that are less than about 2 1/4 inches by about 3 3/8 inches.
2. A data card as in claim 1, wherein the dimensions of said card are in the range of about 1 inch by about 1 inch to about 1 7/8 inches by about 3 inches.
3. A data card as in claim 1, wherein the information storage medium comprises a magnetic stripe.
4. A data card as in claim 3, wherein the magnetic stripe is positioned parallel to an edge of said card.
5. A data card as in claim 3, wherein the magnetic stripe is positioned perpendicular to a largest dimension of said card.
6. A data card as in claim 3, wherein the magnetic stripe comprises two tracks for storing encoded data.
7. A data card as in claim 6, wherein a first of said two tracks comprises data encoded at greater than about 210 bits per inch.
8. A data card as in claim 7, wherein the first of said two tracks comprises data encoded at about 260 bits per inch.
9. A data card as in claim 6, wherein a second of said two tracks comprises data encoded at greater than about 75 bits per inch.
10. A data card as in claim 9, wherein the second of said two tracks comprises data encoded at about 100 bits per inch.

11. A data card as in claim 6, wherein the encoded data is encoded using two-frequency encoding.

12. A data card as in claim 1, wherein said first and second faces define a hole therethrough.

13. A data card as in claim 1, further comprising a core disposed between said first and second faces, wherein said core comprises polyester.

14. A data card as in claim 13, wherein said core comprises about 80% polyester.

15. A data card as in claim 1, wherein the dimensions of said card are about 1 9/16 inches by about 2 9/16 inches.

16. A data card as in claim 1, wherein said first and second faces are devoid of raised lettering.

17. A data card as in claim 1, further comprising lettering printed on at least one of said first and second faces.

18. A data card as in claim 1, wherein the information storage medium comprises a computer chip.

19. A data card as in claim 1, further comprising a tread comprising a plurality of raised dimples for improving the gripability of said card, wherein said plurality of raised dimples are disposed on one of said first and second faces, said one face coming into contact with a user to improve gripability.

20. A data card as in claim 1, further comprising a plurality of craters disposed on one of said first and second faces, each of said plurality of craters comprising: a lip and a center, and wherein the lip of each crater is raised slightly above said one face, and the center of each crater is indented slightly into said one face.

21. A data card comprising a first face, a second face, and a magnetic stripe, wherein the magnetic stripe is positioned parallel to an edge of said card, and the magnetic stripe has a lengthwise dimension of less than about 3.135 inches.

22. A data card as in claim 21, wherein the lengthwise dimension of the magnetic stripe is in the range of about 1 inch to about 3 inches.

23. A data card as in claim 22, wherein the magnetic stripe comprises two tracks for storing encoded data.

24. A data card as in claim 23, wherein a first of said two tracks comprises data encoded at greater than about 210 bits per inch.

25. A data card as in claim 24, wherein the first of said two tracks comprises data encoded at about 260 bits per inch.

26. A data card as in claim 23, wherein a second of said two tracks comprises data encoded at greater than about 75 bits per inch.

27. A data card as in claim 26, wherein the second of said two tracks comprises data encoded at about 100 bits per inch.

28. A data card as in claim 23, wherein the encoded data is encoded using two-frequency encoding.

29. A data card as in claim 21, further comprising a core disposed between said first and second faces, wherein said core comprises polyester.

30. A data card as in claim 29, wherein the core comprises about 80% polyester.

31. A data card as in claim 21, wherein the lengthwise dimension of the magnetic stripe is about 2 9/16 inches.

32. A data card as in claim 21, wherein said first and second faces are devoid of raised lettering.

33. A data card as in claim 21 further comprising lettering printed on at least one of said first and second faces.

34. A data card as in claim 21 further comprising a tread comprising a plurality of raised dimples for improving the gripability of said card, wherein said plurality of raised dimples are disposed on one of said first and second faces, said one face coming into contact with a user to improve gripability.

35. A data card as in claim 21, further comprising a plurality of craters disposed on one of said first and second faces, each of said plurality of craters comprising: a lip and a center, and wherein the lip of each crater is raised slightly above said one face, and the center of each crater is indented slightly into said one face.

36. A data card as in claim 21, wherein said first and second faces define a hole therethrough.

37. A data card as in claim 21, further comprising an angled edge.

38. A data card comprising a first face, a second face, an angled edge, and an information storage medium, wherein a largest dimension of said card is less than about 3 3/8 inches.

39. A data card as in claim 38, wherein the largest dimension of said card is in the range of about 1 7/8 inches to about 3 inches.

40. A data card as in claim 38, wherein the information storage medium comprises a magnetic stripe.

41. A data card as in claim 40, wherein the magnetic stripe is positioned parallel to an edge of said card.

42. A data card as in claim 41, wherein the magnetic stripe comprises two tracks for storing encoded data.

43. A data card as in claim 42, wherein a first of said two tracks comprises data encoded at greater than about 210 bits per inch.

44. A data card as in claim 43, wherein the first of said two tracks comprises data encoded at about 260 bits per inch.

45. A data card as in claim 42, wherein a second of said two tracks comprises data encoded at greater than about 75 bits per inch.

46. A data card as in claim 45, wherein the second of said two tracks comprises data encoded at about 100 bits per inch.

47. A data card as in claim 42, wherein the encoded data is encoded using two-frequency encoding.

48. A data card as in claim 38, wherein said first and second faces define a hole therethrough.

49. A data card as in claim 38, further comprising a core disposed between said first and second faces, wherein said core comprises polyester.

50. A data card as in claim 49, wherein said core comprises about 80% polyester.

51. A data card as in claim 38, wherein said first and second faces are devoid of raised lettering.

52. A data card as in claim 38, further comprising lettering printed on at least one of said first and second faces.

53. A data card as in claim 38, wherein the information storage medium comprises a computer chip.

54. A data card as in claim 38, further comprising a tread comprising a plurality of raised dimples for improving the gripability of said card, wherein said plurality of raised dimples are disposed on one of said first and second faces, said one face coming into contact with a user to improve gripability.

55. A data card as in claim 38, further comprising a plurality of craters disposed on one of said first and second faces, each of said plurality of craters comprising: a lip and a center, and wherein the lip of each crater is raised slightly above said one face, and the center of each crater is indented slightly into said one face.

56. A data card as in claim 40, wherein the magnetic stripe is positioned perpendicular to the largest dimension of said card.

57. A data card as in claim 40, wherein the magnetic stripe is positioned parallel to said angled edge.



ABSTRACT

A data card is reduced in size from the conventional standard size credit card. Accessibility of the card is enhanced because the card may be stored in a separate location from conventionally sized cards, such as on a key-chain or similar device. The card of the present invention has a means for storing information, such as a magnetic stripe or computer chip.

Please type a plus sign (+) inside this box → Approved for use through 10/31/2002 OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number

**DECLARATION FOR UTILITY OR
DESIGN
PATENT APPLICATION
(37 CFR 1.63)**

Declaration Submitted with Initial Filing Declaration Submitted after Initial Filing (surcharge (37 CFR 1.16 (e)) required)

OR

Attorney Docket Number	016762.0217-US01
First Named Inventor	Jamily Pentz
COMPLETE IF KNOWN	
Application Number	Not Yet Assigned
Filing Date	
Group Art Unit	N/A
Examiner Name	Not Yet Assigned

As a below named inventor, I hereby declare that:

My residence, mailing address, and citizenship are as stated below next to my name.

I believe I am the original, first and sole inventor (if only one name is listed below) or an original, first and joint inventor (if plural names are listed below) of the subject matter which is claimed and for which a patent is sought on the invention entitled:

DATA CARD

(Title of the Invention)

the specification of which

is attached hereto

OR

was filed on (MM/DD/YYYY) as United States Application Number or PCT International

Application No. and was amended on (MM/DD/YYYY) (if applicable).

I hereby state that I have reviewed and understand the contents of the above identified specification, including the claims, as amended by any amendment specifically referred to above.

I acknowledge the duty to disclose information which is material to patentability as defined in 37 CFR 1.56, including for continuation-in-part applications, material information which became available between the filing date of the prior application and the national or PCT international filing date of the continuation-in-part application.

I hereby claim foreign priority benefits under 35 U.S.C. 119(a)-(d) or (f), or 365(b) of any foreign application(s) for patent, inventor's or plant breeder's rights certificate(s), or 365 (a) of any PCT international application which designated at least one country other than the United States of America, listed below and have also identified below, by checking the box, any foreign application for patent, inventor's or plant breeder's rights certificate(s), or of any PCT international application having a filing date before that of the application on which priority is claimed.

Prior Foreign Application Number(s)	Country	Foreign Filing Date (MM/DD/YYYY)	Priority Not Claimed	Certified Copy Attached?
			<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>	<input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/> <input type="checkbox"/>
<input type="checkbox"/>	Additional foreign application numbers are listed on a supplemental priority data sheet PTO/SB/02B attached hereto			

Please type a plus sign (+) inside this box →

Approved for use through 10/31/2002 OMB 0651-0032
U.S. Patent and Trademark Office, U.S. DEPARTMENT OF COMMERCE
Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION — Utility or Design Patent Application

Direct all correspondence to Customer Number or Bar Code Label **26853** OR Correspondence address below

Name

Address

City

State

ZIP

Country


Telephone

Fax

I hereby declare that all statements made herein of my own knowledge are true and that all statements made on information and belief are believed to be true; and further that these statements were made with the knowledge that willful false statements and the like so made are punishable by fine or imprisonment, or both, under 18 U.S.C. 1001 and that such willful false statements may jeopardize the validity of the application or any patent issued thereon.

NAME OF SOLE OR FIRST INVENTOR: A petition has been filed for this unsigned inventor

Given Name **Jamily** Family Name or Surname **Pentz**
(first and middle [if any])

Inventor's Signature 

Date **10/26/2001**

Residence: City **Tega Cay**

State **SC**

Country

US

Citizenship

Mailing Address:

4114 Marquesas Avenue

City **Tega Cay**

State **SC**

ZIP **29708**

Country

NAME OF SECOND INVENTOR: A petition has been filed for this unsigned inventor

Given Name **Emmet** Family Name or Surname **Burns**
(first and middle [if any])

Inventor's Signature 

Date **August 20, 2001**

Residence: City **Charlotte**

State **NC**

Country

US

Citizenship

Mailing Address:

**Bank of America
NC1-022-17-01
201 N. Tryon Street**

City **Charlotte**

State **NC**

ZIP **28255**

Country

Additional inventors are being named on the **1** supplemental Additional Inventor(s) sheet(s) PTO/SB/02A attached hereto

Please type a plus sign (+) inside this box → Approved for use through 10/31/2002. OMB 0651-0032
U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

DECLARATION		ADDITIONAL INVENTOR(S) Supplemental Sheet Page 1 of 1	
--------------------	--	--	--

Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle [if any]) <i>Richard J.</i>		Family Name or Surname <i>10/25/01</i>	
Inventor's Signature	Date <i>10/25/01</i>		
Residence: City Highland Park	State IL	Country	Citizenship US
Mailing Address: 148 Whistler Road			
City Highland Park	State IL	ZIP 60035	Country
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle [if any]) <i>R. Bruce</i>		Family Name or Surname <i>Montgomery</i>	
Inventor's Signature	Date <i>10/31/01</i>		
Residence: City Charlotte	State NC	Country	Citizenship US
Mailing Address: 10207 Wildbracken Court			
City Charlotte	State NC	ZIP 28210	Country
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle [if any]) <i>A. Allen</i>		Family Name or Surname <i>Kendle</i>	
Inventor's Signature	Date <i>9/18/01</i>		
Residence: City North Carolina	State	Country	Citizenship US
Mailing Address: 2400 Valencia Terrace			
City North Carolina	State	ZIP 28226	Country
Name of Additional Joint Inventor, if any:		<input type="checkbox"/> A petition has been filed for this unsigned inventor	
Given Name (first and middle [if any])		Family Name or Surname	
Inventor's Signature	Date		
Residence: City	State	Country	Citizenship
Mailing Address:			
City	State	ZIP	Country

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Patent Application of:
Jamily Pentz, et al.

Application No.: Not Yet Assigned

Group Art Unit: N/A

Filed: Herewith

Examiner: Not Yet Assigned

For: DATA CARD

POWER OF ATTORNEY FROM ASSIGNEE

Commissioner for Patents
Washington, DC 20231

Dear Sir:

Bank of America Corporation, assignee of the entire right title and interest in the above-identified application by assignment, submitted herewith, hereby appoints the members of the firm of Covington & Burling, a firm composed of:

Paul J. Berman	36,744	Ann O. McGeehan	45,839	Christopher N. Sipes	39,837
Kurt Geoffrey Calia	38,702	Jeannie M. Perron	31,180	Lee J. Tiedrich	42,184
Richard P. Dulik	40,598	C. Edward Polk	45,830	Henry P. Ting	46,278
Thomas W. Krause	40,335	Andrea G. Reister	36,253	Grady L. White	40,874
Scott B. Markow	46,899	David P. Ruschke	40,151	Anthony S. Yoo	45,540
Michael A. Springs	41,322				

as its attorneys with full power of substitution to prosecute this application and to transact all business in the Patent and Trademark Office in connection therewith.

The assignee certifies that it has reviewed the assignment and to the best of the assignee's knowledge and belief, title is in the assignee.

Please direct all correspondence regarding this application to the following:

COVINGTON & BURLING
Attn: Andrea G. Reister
1201 Pennsylvania Avenue, N.W.
Washington, DC 20004-2401
Telephone: (202) 662-6000
Fax: (202) 662-6291

For: Bank of America Corporation

Michael A. Springs
Michael A. Springs, Esq.
Assistant General Counsel

Dated:

8/27/01

STATEMENT UNDER 37 CFR 3.73(b)

Applicant/Patent Owner: Jamily Pentz, et al.

Application No./Patent No.: To be Assigned Filed/Issue Date: Herewith

Entitled: DATA CARD

Bank of America Corporation , a Corporation
(Name of Assignee) Type of Assignee, e.g., corporation, partnership, university, government agency, etc

states that it is:

1. the assignee of the entire right, title, and interest; or

2. an assignee of less than the entire right, title and interest.
The extent (by percentage) of its ownership interest is %

in the patent application/patent identified above by virtue of either:

A. [x] An assignment from the inventor(s) of the patent application/patent identified above. The assignment was recorded in the United States Patent and Trademark Office at Reel _____, Frame _____, or for which a copy thereof is attached.

OR

B. [] A chain of title from the inventor(s), of the patent application/patent identified above, to the current assignee as shown below:

1. From: _____ To: _____
The document was recorded in the United States Patent and Trademark Office at
Reel _____, Frame _____, or for which a copy thereof is attached.

2. From: _____ To: _____
The document was recorded in the United States Patent and Trademark Office at
Reel _____, Frame _____, or for which a copy thereof is attached.

3. From: _____ To: _____
The document was recorded in the United States Patent and Trademark Office at
Reel _____, Frame _____, or for which a copy thereof is attached.

Additional documents in the chain of title are listed on a supplemental sheet.

Copies of assignments or other documents in the chain of title are attached.
[NOTE: A separate copy (*i.e.*, the original assignment document or a true copy of the original document) must be submitted to Assignment Division in accordance with 37 CFR Part 3, if the assignment is to be recorded in the records of the USPTO. See MPEP 302.08]

The undersigned (whose title is supplied below) is authorized to act on behalf of the assignee.

8/27/01

Date

Michael A. Springs, Esq.

Typed or printed name

150

Signature

Assistant General Counsel

Title

Supplemental Application Data Sheet
(Multiple Inventors with Representation, Continuity and Priority)
Page 1 of 3 Pages

Inventor Information

Inventor One Given Name:	Jamily
Family Name:	Pentz
Postal Address Line One:	4114 Marquesas Avenue
City:	Tega Cay
State or Province:	South Carolina
Postal or Zip Code:	29708
Citizenship Country:	USA
Inventor Two Given Name:	Emmet
Family Name:	Burns
Postal Address Line One:	Bank of America
Postal Address Line Two:	NC1-022-17-01
Postal Address Line Three:	201 N. Tryon Street
City:	Charlotte
State or Province:	North Carolina
Postal or Zip Code:	28255
Citizenship Country:	USA
Inventor Three Given Name:	Richard J.
Family Name:	Collins
Postal Address Line One:	148 Whistler Road
City:	Highland Park
State or Province:	Illinois
Postal or Zip Code:	60035
Citizenship Country:	USA
Inventor Four Given Name:	R. Bruce
Family Name:	Montgomery
Postal Address Line One:	10207 Wildbracken Court
City:	Charlotte
State or Province:	North Carolina
Postal or Zip Code:	28210
Citizenship Country:	USA
Inventor Five Given Name:	A. Allen
Family Name:	Kendle
Postal Address Line One:	2400 Valencia Terrace
City:	<u>Charlotte</u>
State or Province:	North Carolina
Postal or Zip Code:	28226
Citizenship Country:	USA

Supplemental Application Data Sheet
(Multiple Inventors with Representation, Continuity and Priority)
Page 2 of 3 Pages

Correspondence Information

Name Line One: Covington & Burling
Name Line Two: Patent Docketing
Address Line One: 1201 Pennsylvania Avenue, NW
City: Washington
State or Province: D.C.
Postal or Zip Code: 20004-2401
Telephone One: 202.662.6000
Fax: 202.662.6291
Electronic Mail:

Application Information

Title Line One: Data Card
Total Drawing Sheets: 11
Formal Drawings?: No
Application Type: Utility
Docket Number: 016762.0217-US01

Representative Information

Representative Customer Number: 26853

Continuity Information

This application is a: Continuation of
>Application One: 09/611,320
Filing Date: July 6, 2000

>Application Two: 29/141,685
Filing Date: May 11, 2001

>Application Three: 29/141,652
Filing Date: May 11, 2001

>Application Four: 29/141,645
Filing Date: May 11, 2001

>Application Five: 29/141,642
Filing Date: May 11, 2001

Supplemental Application Data Sheet
(Multiple Inventors with Representation, Continuity and Priority)
Page 3 of 3 Pages

>Application Six:	29/141,688
Filing Date:	May 11, 2001
>Application Seven:	29/141,704
Filing Date:	May 11, 2001
>Application Eight:	29/141,703
Filing Date:	May 11, 2001
>Application Nine:	29/141,691
Filing Date:	May 11, 2001
>Application Ten:	29/141,702
Filing Date:	May 11, 2001
>Application Eleven:	29/141,692
Filing Date:	May 11, 2001
>Application Twelve:	29/141,701
Filing Date:	May 11, 2001
>Application Thirteen:	29/141,700
Filing Date:	May 11, 2001
>Application Fourteen:	29/141,693
Filing Date:	May 11, 2001
>Application Fifteen:	29/141,699
Filing Date:	May 11, 2001
>Application Sixteen:	29/142,203
Filing Date:	May 22, 2001

Prior U.S. Applications

U.S. Application One:	60/263,756
Filing Date:	January 25, 2001
Country:	USA
Priority Claimed:	Yes

Patent Application Initial Information Data Sheet
(Multiple Inventors with Representation, Continuity and Priority)

Inventor Information

Inventor One Given Name:	Jamily
Family Name:	Pentz
Postal Address Line One:	4114 Marquesas Avenue
City:	Tega Cay
State or Province:	South Carolina
Postal or Zip Code:	29708
Citizenship Country:	USA
Inventor Two Given Name:	Emmet
Family Name:	Burns
Postal Address Line One:	Bank of America
Postal Address Line Two:	NC1-022-17-01
Postal Address Line Three:	201 N. Tryon Street
City:	Charlotte
State or Province:	North Carolina
Postal or Zip Code:	28255
Citizenship Country:	USA
Inventor Three Given Name:	Richard J.
Family Name:	Collins
Postal Address Line One:	148 Whistler Road
City:	Highland Park
State or Province:	Illinois
Postal or Zip Code:	60035
Citizenship Country:	USA
Inventor Four Given Name:	R. Bruce
Family Name:	Montgomery
Postal Address Line One:	10207 Wildbracken Court
City:	Charlotte
State or Province:	North Carolina
Postal or Zip Code:	28210
Citizenship Country:	USA
Inventor Five Given Name:	A. Allen
Family Name:	Kendle
Postal Address Line One:	2400 Valencia Terrace
City:	
State or Province:	North Carolina
Postal or Zip Code:	28226
Citizenship Country:	USA

Patent Application Initial Information Data Sheet
(Multiple Inventors with Representation, Continuity and Priority)
Page 2

Correspondence Information

Name Line One: Covington & Burling
Name Line Two: Patent Docketing
Address Line One: 1201 Pennsylvania Avenue, NW
City: Washington
State or Province: D.C.
Postal or Zip Code: 20004-2401
Telephone One: 202.662.6000
Fax: 202.662.6291
Electronic Mail:

Application Information

Title Line One: Data Card
Total Drawing Sheets: 11
Formal Drawings?: No
Application Type: Utility
Docket Number: 016762.0217-US01

Representative Information

Representative Customer Number: 26853

Continuity Information

This application is a: Continuation of
>Application One: 09/611,320
Filing Date: July 6, 2000

>Application Two: 29/141,685
Filing Date: May 11, 2001

>Application Three: 29/141,652
Filing Date: May 11, 2001

>Application Four: 29/141,645
Filing Date: May 11, 2001

>Application Five: 29/141,642
Filing Date: May 11, 2001

Patent Application Initial Information Data Sheet
(Multiple Inventors with Representation, Continuity and Priority)
Page 3

>Application Six:	29/141,688
Filing Date:	May 11, 2001
>Application Seven:	29/141,704
Filing Date:	May 11, 2001
>Application Eight:	29/141,703
Filing Date:	May 11, 2001
>Application Nine:	29/141,691
Filing Date:	May 11, 2001
>Application Ten:	29/141,702
Filing Date:	May 11, 2001
>Application Eleven:	29/141,692
Filing Date:	May 11, 2001
>Application Twelve:	29/141,701
Filing Date:	May 11, 2001
>Application Thirteen:	29/141,700
Filing Date:	May 11, 2001
>Application Fourteen:	29/141,693
Filing Date:	May 11, 2001
>Application Fifteen:	29/141,699
Filing Date:	May 11, 2001
>Application Sixteen:	29/142,203
Filing Date:	May 22, 2001

Prior U.S. Applications

U.S. Application One:	60/263,756
Filing Date:	January 25, 2001
Country:	USA
Priority Claimed:	Yes

09/988151

235
487

10




FIG. 1A

09/988151
10
11
12
13
14
15

17

16




FIG. 1B




FIG 2A




FIG 2B




FIG 3A

FIG 3B




FIG 4A



FIG 4B




FIG 4C



FIG 4D

50




FIG 5A

51




FIG 6A

61

62

60




FIG. 7A




FIG. 7B




FIG. 7C





FIG. 9A






FIG. 9B



PRINT OF DRAWINGS
AS ORIGINALS

FIG. 9C



PRINT OF DRAWINGS
AS ORIGINALLY RECEIVED

Dimensions in millimetres (inches)




FIG. 10

PRINT OF DRAWINGS
AS ORIGINALLY ISSUED




FIG. 11





FIG. 12

FIG 13A



FIG. 13B



131

2 9/16

1 7/16




FIG. 1A









FIG. 1B

Figs. 27










FIG. 7A




FIG. 7B




FIG. 7C




FIG. 8A




FIG. 8B

FIG. 9A




FIG. 9B





FIG. 9C



Dimensions in millimetres (inches)




FIG. 10

PROPRIETARY RECORDING TAPE
4 MIL POLYESTER BACKING
1 MIL POLYURETHANE COATING





FIG. 11



For use of tracks 1 and 2: $a = 11.89 (0.468) \text{ min}$
 For use of tracks 1, 2, and 3: $a = 15.95 (0.628) \text{ min}$

FIG. 12

FIG 13A




139

130



四〇

1915



29/16

故其聲氣之和，則其氣之和也。故其氣之和，則其聲氣之和也。